


°dot



material aluminium coated
 weight 80gr / 0.17lb
 voltage 24Vdc
 cri >90
 wattage 3,6W
 dali not supported
 rotation 4 steps of 90°
 inclination 90°
 certifications CE, ENEC
 classifications IP20




DOT.L.B.D.V

Led	WW WW2 NW2	2700K 3,6W 100 lm - 2353 cd - 8° 3000K 3,6W 105 lm - 2670 cd - 8° 4000K 3,6W 110 lm - 2800 cd - 8°
Body color	BK WH AL	black matt ral 9011 white matt ral 9016 aluminium color ral 9006 (on request only)
Dimming	OC	track overall control. dimming possible with 0/1-10V, potentiometer, on 2 circuits (see pag. 76)
Version	T BI	track mount built in monopoint (plasterkit required)
Accessories	PL.DOT	monopoint plasterkit °dot

°dot turn ^{NEW}

material aluminium coated
 weight 170gr / 0.37lb
 voltage 24Vdc
 cri >90
 wattage 3W
 dali supported DT6
 rotation 355°
 inclination 90°
 certifications CE 
 classifications IP20 



DOT.TURN.L.B.D.V

Led	WW	2700K 3,6W 100 lm - 2353 cd - 8°
	WW2	3000K 3,6W 105 lm - 2670 cd - 8°
	NW2	4000K 3,6W 110 lm - 2800 cd - 8°
Body color	BK	black matt ral 9011
	WH	white matt ral 9016
	AL	aluminium color ral 9006 (on request only)
Dimming	IC	fixtures individually dimmable, controlled by DALI DT6 track overall control. dimming possible with 0/1-10V, potentiometer, on 2 circuits (see pag. 76)
	OC	
Version	T	track mount
	BI	built in monopoint (plasterkit required)
Accessories	PL.DOTTURN	monopoint plasterkit °dot turn

power supply 24Vdc

PS.24.XX.SM.HLG 1-10V dimming, CE, cUL certified, 90-305VAC

40	W	171*61.5*36.8 mm (L*W*H)
60	W	171*61.5*36.8 mm
80	W	195.6*61.5*38.8 mm
100	W	220*68*38.8 mm
150	W	228*68*38.8 mm
240	W	244.2*68*38.8 mm
320	W	252*90*43.8 mm
600	W	280*144*48.5mm

DAP04 dali adaptor for dali control of power supply HLG (165*46*23 mm)


PS.24.XX.SM.ELG 0-10V dimming, CE, cUL, CCC certified, 110-305VAC

at 240V	at 110V	
75W	60W	180*63*35.5mm (L*W*H)
100W	70W	199*63*35.5mm
150W	105W	219*63*35.5mm
200W	150W	244*71*37.5mm
240W	180W	244*71*37.5mm

PS.24.XX.SM.ELG.DA DALI dimming, CE, cUL, CCC certified, 110-305VAC

at 240V	at 110V	
75W	60W	180*63*35.5mm (L*W*H)
100W	70W	199*63*35.5mm
150W	105W	219*63*35.5mm
200W	150W	244*71*37.5mm
240W	180W	244*71*37.5mm

PS.24.SM.B.DIM Potentiometer dimming button (0-10V/1-10V)



LDIM.24V DIN rail mount dimmodule 24 VDC Max 240W controlled by 0/1-10V or potentiometer (width 25mm)

