




BOULY WALL/CEILING D+B



Material

aluminium - PMMA

Materiaal

aluminium - PMMA

Matériau

aluminium - PMMA



Finish

black - chrome - gold - grey - ivory - white
PMMA : transparent
lens : PMMA

Afwerking

zwart - chroom - goud - grijs - ivoor - wit
PMMA : transparent
lens : PMMA

Finition

noir - chrome - or - gris - ivoire - blanc
PMMA : transparent
lentille : PMMA

Lightsource

4 x power LED (included) 1.2W
cold white : 6000K - 440lm - CRI >75
4 x LED (included) 0.96W
warm white : 2700K - 456lm - CRI >93

Lichtbron

4 x power LED (inclusief) 1.2W
koud wit : 6000K - 440lm - CRI >75
4 x LED (inclusief) 0.96W
warm wit : 2700K - 456lm - CRI >93

Source lumineuse

4 x power LED (inclus) 1.2W
blanc froid : 6000K - 440lm - CRI >75
4 x LED (inclus) 0.96W
blanc chaud : 2700K - 456lm - CRI >93

Connection

230V - driver included (in base)

Aansluiting

230V - voeding inclusief (in basis)

Connexion

230V - convertisseur inclus (dans la base)

Specifications

indoor
wall or ceiling mounting
class I
IP40

Specificaties

binnen
wand- of plafondmontage
klasse I
IP40

Spécifications

intérieur
applique ou plafonnier
classe I
IP40