



(/fileadmin/assets/images/products/article-image/600px/611974.0031.jpg)

611974.0031

**Series**

Home 201

**Type of Installation**

ground installation

**Colour**

anthracite metallic

**European Article number EAN**

4051859151647

Bollard with continuous root. Housing: pressure die-cast aluminium, powder-coated. Pole top can be swivelled. Diffuser: plastic (polycarbonate), opal. Driver included. LED included.

[Technical Specifications](#)[Downloads](#)

## Technical Specifications

### Electrical:

**Luminaire efficacy**

43

**Control gear**

Converter

**Voltage**

200 - 240 V / 50 - 60 Hz

**System power**

18 W

**Luminaires on B10A fuse**

50

**Luminaires on B16A fuse**

80

**Inrush current / inrush current duration**30 A / 15  $\mu$ s

---

### Lighting technology:

**UGR**

24.8

**Luminaire beam angle**

118°

**Rated luminous flux**

770 lm

**Colour rendering index (CRI)**

84

---

### Approbations:

**Type of Protection**

IP 54

**Protection Class**

I

**Glow Wire Test**

850°C - 30 seconds

**Impact Protection**

IK06 (1 Joule)

**Safety marks**

F-mark

**Other Marks**

WEEE mark

**Ambient temperature min.**

-20 °C

**Ambient temperature max.**

25 °C

**Country Code**

CE

**Energy efficiency class LED**

A+

**Energy class of included lamp**A+ □

---

**Lamps:****Socket****Light colour**

830

**Colour temperature**

3000K

**Lifetime**

25000 h (L70/B50)

**Number of lamps**

10

**Lamp**

LED

---

**Dimensions:****Diameter D**

200 mm

**Length L**

1,150 mm

**Height H**

900 mm

**Recess depth HE**

250 mm

**Weight**

1.9 kg

