



(/fileadmin/assets/images/products/article-image/600px/611975.0031.jpg)

611975.0031

Series

Home 202

Type of Installation

pedestal mount

Colour

anthracite metallic

European Article number EAN

4051859151654

Bollard for socket mounting. Housing: pressure die-cast aluminium, powder-coated. Diffuser: plastic (polycarbonate), opal. Driver included. LED included.

[Technical Specifications](#)[Downloads](#)

Technical Specifications

Electrical:

Luminaire efficacy

33

Control gear

Converter

Voltage

200 - 240 V / 50 - 60 Hz

System power

9 W

Luminaires on B10A fuse

110

Luminaires on B16A fuse

180

Inrush current / inrush current duration25 A / 13 μ s

Lighting technology:

UGR

32.9

Luminaire beam angle

112°/180°

Rated luminous flux

290 lm

Colour rendering index (CRI)

82

Approbations:

Type of Protection

IP 54

Protection Class

I

Glow Wire Test

850°C - 30 seconds

Impact Protection

IK06 (1 Joule)

Safety marks

F-mark

Other Marks

WEEE mark

Ambient temperature min.

-20 °C

Ambient temperature max.

25 °C

Country Code

CE

Energy efficiency class LED

A+

Energy class of included lamp

A+

Lamps:**Socket****Light colour**

830

Colour temperature

3000K

Lifetime

25000 h (L70/B50)

Number of lamps

1

Lamp

LED

Dimensions:**Length L**

40 mm

Width B

120 mm

Height H

350 mm

Weight

1.11 kg

