

(/fileadmin/assets/images/products/article-image/600px/451180.009.jpg)

Planox ECO

451214.009

Series Planox ECO

Type of Installation Ceiling mounting, Pendant, Wall (surface)

Colour

grey

European Article number EAN 4051859249979

Side panels: grey plastic, polycarbonate. Diffuser: opal plastic, polycarbonate. Converter: encapsulated, integrated and permanently connected to the diffuser and side panel. Cable screw fittings for convenient wiring. Quarter turn lock on both sides for simple installation Luminaire with integrated through wiring for lining up further (safety class II) luminaires. Ceiling mounting bracket made of stainless steel and triangular bracket for pendant mounting included in the scope of delivery. LED included.

Technical Specifications Downloads Light Calculator Accessories

Technical Specifications

Electrical:

Luminaire efficacy 128 lm/W

Control gear Converter

Voltage 220 - 240 V / 50 - 60 Hz

System power

53 W

Luminaires on B10A fuse

3

Luminaires on B16A fuse 5

. . .

Luminaires on C10A fuse

6

Luminaires on C16A fuse

11

Inrush current / inrush current duration 14.3 A / 84 μs

Lighting technology:

UGR 25.6 Luminaire beam angle 178°/115°

Rated luminous flux 6,750 lm

Colour rendering index (CRI) 80

Approbations:

Type of Protection IP 66

Protection Class

Glow Wire Test 850°C - 30 seconds

Impact Protection IK08 (5 Joule)

Safety marks D-mark **Other Marks** WEEE mark

Ambient temperature min. -30 °C Ambient temperature max.

50 °C

Country Code

CE

Energy efficiency class LED A+

Energy class of included lamp A+

Lamps:
Socket
Light colour 840
Colour temperature 4000K
Lifetime 50000 h (L80/B10)
Colour consistency (McAdam) 6
Number of lamps 1
Lamp LED

Dimensions:

Length L 1,669 mm

Width B

61 mm

Height H 50 mm

Weight

1,060 g

