



(/fileadmin/assets/images/products/article-image/600px/901573.002.jpg)

## Toledo

### 901573.002

**Series**

Toledo

**Type of Installation**

Recessed ceiling mounting

**Colour**

white

**European Article number EAN**

4051859145929

Bezel ring: powder coated die cast aluminium. Housing: plastic (UV resistant polycarbonate). Diffuser: opal plastic (UV resistant polycarbonate), shockproof. Spring fastening system. Passive cooling. Suitable for through wiring. Converter included. LED included.

[Technical Specifications](#)

[Downloads](#)

[Light Calculator](#)

## Technical Specifications

**Electrical:**

**Luminaire efficacy**

95 lm/W

**Control gear**

Converter

**Voltage**

220 - 240 V / 50 - 60 Hz

**System power**

8 W

**Luminaires on B10A fuse**

20

**Luminaires on B16A fuse**

33

**Luminaires on C10A fuse**

41

**Luminaires on C16A fuse**

66

**Inrush current / inrush current duration**2.42 A / 40  $\mu$ s

## Lighting technology:

**UGR**

26.5

**Luminaire beam angle**

102°

**Rated luminous flux**

760 lm

**Colour rendering index (CRI)**

80

## Approbations:

**Type of Protection**

IP 44

**Protection Class**

II

**Glow Wire Test**

750°C - 30 seconds

**Impact Protection**

IK05 (0,70 Joule)

**Safety marks**

F-mark

**Other Marks**

WEEE mark

**Ambient temperature min.**

-30 °C

**Ambient temperature max.**

40 °C

**Country Code**

CE

**Energy efficiency class LED**

A+

**Energy class of included lamp**

A+

---

**Lamps:****Socket****Light colour**

827

**Colour temperature**

2700K

**Lifetime**

50000 h (L70/B50)

**Colour consistency (McAdam)**

4

**Number of lamps**

1

**Lamp**

LED

---

**Dimensions:****Diameter D**

130 mm

**Height H**

2 mm

**Cut-out DA**

105 mm

**Recess depth HE**

100 mm

**Ceiling thickness**

1-25 mm

**Weight**

185 g

