



(/fileadmin/assets/images/products/article-image/600px/901574.002.jpg)

Toledo

901574.002.76

Series

Toledo

Type of Installation

Recessed ceiling mounting

Colour

white

European Article number EAN

4051859218296

Bezel ring: powder coated die cast aluminium. Housing made of plastic (UV-resistant polycarbonate). Diffuser made of plastic (UV resistant polycarbonate) opal, shockproof. With spring fastening system. Passive cooling. Suitable for through-wiring. External converter. Lamp (LED) included.

[Technical Specifications](#)

[Downloads](#)

[Light Calculator](#)

Technical Specifications

Electrical:

Luminaire efficacy

95 lm/W

Control gear

DALI

Voltage

220 - 240 V / 0 Hz, 50 - 60 Hz

System power

18 W

Luminaires on B10A fuse

45

Luminaires on B16A fuse

80

Inrush current / inrush current duration17 A / 50 μ s**Ripple current / Flicker**

1 %

Lighting technology:**UGR**

28.2

Luminaire beam angle

102°

Rated luminous flux

1,700 lm

Colour rendering index (CRI)

80

Approbations:**Type of Protection**

IP 44

Protection Class

II

Glow Wire Test

750°C - 30 seconds

Impact Protection

IK05 (0,70 Joule)

Safety marks

F-mark

Other Marks

WEEE mark

Country Code

CE

Energy efficiency class LED

A+

Energy class of included lamp

A+

Lamps:**Light colour**

827

Colour temperature

2700K

Lifetime

50000 h (L70/B50)

Colour consistency (McAdam)

4

Number of lamps

1

Lamp

LED

Dimensions:**Diameter D**

172 mm

Height H

2 mm

Cut-out DA

150 mm

Recess depth HE

140 mm

Ceiling thickness

1-25 mm

Dimensions

L 178 x B 92 x H 30 mm

Weight

519 g

