



(/fileadmin/assets/images/products/article-image/600px/221175.002.jpg)

221175.002

Series

Home 501

Type of Installation

Ceiling mounting, Wall (surface)

Colour

white

European Article number EAN

4051859168171

Fitting galvanised sheet steel, with bayonet mounting. Housing plastic (PC). Diffuser plastic, opal (PC). Housing and diffuser permanently connected.

[Technical Specifications](#)

[Downloads](#)

[Light Calculator](#)

Technical Specifications

Electrical:**Luminaire efficacy**

92

Control gear

EB

Voltage

220 - 240 V / 50 Hz

System power

18 W

Luminaires on B10A fuse

16

Luminaires on B16A fuse

26

Luminaires on C10A fuse

27

Luminaires on C16A fuse

44

Inrush current / inrush current duration

31.6 A

Lighting technology:**UGR**

21.8

Luminaire beam angle

113°

Rated luminous flux

1,650 lm

Colour rendering index (CRI)

80

Approbations:**Type of Protection**

IP 40

Protection Class

I

Glow Wire Test

850°C - 30 seconds

Impact Protection

IK06 (1 Joule)

Safety marks

F-mark

Other Marks

WEEE mark

Country Code

CE

Energy efficiency class LED

A+

Energy class of included lamp

A+

Lamps:

Socket**Light colour**

830

Colour temperature

3000K

Lifetime

35000 h (L70/B50)

Number of lamps

1

Lamp

LED

Dimensions:

Diameter D

300 mm

Height H

48 mm

Weight

0.93 kg

