



(/fileadmin/assets/images/products/article-image/600px/742129.002.jpg)

## Calido Clickbeam Mini

742129.002

### **Series**

Calido Clickbeam Mini

### **Type of Installation**

Track on ceiling

### **Colour**

Traffic white, matt (RAL 9016)

### **European Article number EAN**

4051859364320

Housing pressure extruded aluminium profile powder-coated. Cover and lever arm plastic. 356° horizontal turning and 90° vertical pivoting. Heat-resistant plastic ring black. Special polycarbonate lens suitable for various beam angles. Lens position adjustable via pressure mechanism for setting beam angle.</>Passive cooling. With multi-adapter for 3-phase 230 V power tracks. Ceiling installation. Lamp (LED) included in scope of delivery.

[Technical Specifications](#)

[Downloads](#)

[Light Calculator](#)

[Accessories](#)

## Technical Specifications

**Electrical:****Luminaire efficacy**

96 lm/W

**Control gear**

Converter

**Voltage**

220 - 240 V / 50 - 60 Hz

**System power**

12 W

**Luminaires on B10A fuse**

11

**Luminaires on B16A fuse**

18

**Luminaires on C10A fuse**

22

**Luminaires on C16A fuse**

36

**Inrush current / inrush current duration**

4.38 A / 24 µs

---

**Lighting technology:****UGR**

19.9

**Luminaire beam angle**

21° - 34° Clickbeam

**Rated luminous flux**

1,150 lm

**Colour rendering index (CRI)**

80

---

**Approbations:****Type of Protection**

IP 20

**Protection Class**

II

**Safety marks**

F-mark

**Other Marks**

WEEE mark

**Country Code**

CE

**Energy efficiency class LED**

A++

**Energy class of included lamp**

A++

---

**Lamps:****Socket****Light colour**

828

**Colour temperature**

2800K

**Lifetime**

25000 h (L70/B50)

**Colour consistency (McAdam)**

3

**Number of lamps**

1

**Lamp**

LED

---

**Dimensions:****Diameter D**

50 mm

**Height H**

132 mm

**Weight**

180 g

