



(/fileadmin/assets/images/products/article-image/600px/742129.003.jpg)

Calido Clickbeam Mini

742129.003.1

Series

Calido Clickbeam Mini

Type of Installation

Track on ceiling

Colour

deep black, matt (RAL 9005)

European Article number EAN

4051859364368

Housing pressure extruded aluminium profile powder-coated. Cover and lever arm plastic. 356° horizontal turning and 90° vertical pivoting. Heat-resistant plastic ring black. Special polycarbonate lens suitable for various beam angles. Lens position adjustable via pressure mechanism for setting beam angle. Passive cooling. With multi-adapter for 3-phase 230 V power tracks. Ceiling installation. Lamp (LED) included in scope of delivery.

[Technical Specifications](#)

[Downloads](#)

[Light Calculator](#)

[Accessories](#)

Technical Specifications

Electrical:**Luminaire efficacy**

105 lm/W

Control gear

Converter

Voltage

220 - 240 V / 50 - 60 Hz

System power

12 W

Luminaires on B10A fuse

11

Luminaires on B16A fuse

18

Luminaires on C10A fuse

22

Luminaires on C16A fuse

36

Inrush current / inrush current duration

4.38 A / 24 µs

Lighting technology:**UGR**

20.2

Luminaire beam angle

21° - 34° Clickbeam

Rated luminous flux

1,250 lm

Colour rendering index (CRI)

80

Approbations:**Type of Protection**

IP 20

Protection Class

II

Safety marks

F-mark

Other Marks

WEEE mark

Country Code

CE

Energy efficiency class LED

A++

Energy class of included lamp

A++

Lamps:**Socket****Light colour**

840

Colour temperature

4000K

Lifetime

25000 h (L70/B50)

Colour consistency (McAdam)

3

Number of lamps

1

Lamp

LED

Dimensions:**Diameter D**

50 mm

Height H

132 mm

Weight

180 g

