



(/fileadmin/assets/images/products/article-image/600px/742130.002.jpg)

Calido Clickbeam Midi

742130.002

Series

Calido Clickbeam Midi

Type of Installation

Track on ceiling

Colour

Traffic white, matt (RAL 9016)

European Article number EAN

4051859364382

Housing pressure extruded aluminium profile powder-coated. Cover and lever arm plastic. 356° horizontal turning and 90° vertical pivoting. Heat-resistant plastic ring black. Special polycarbonate lens suitable for various beam angles. Lens position adjustable via pressure mechanism for setting beam angle.</>Passive cooling. With multi-adapter for 3-phase 230 V power tracks. Ceiling installation. Lamp (LED) included in scope of delivery.

[Technical Specifications](#)

[Downloads](#)

[Light Calculator](#)

[Accessories](#)

Technical Specifications

Electrical:**Luminaire efficacy**

78 lm/W

Control gear

Converter

Voltage

220 - 240 V / 50 - 60 Hz

System power

25 W

Luminaires on B10A fuse

7

Luminaires on B16A fuse

12

Luminaires on C10A fuse

15

Luminaires on C16A fuse

25

Inrush current / inrush current duration6.4 A / 16 μ s

Lighting technology:**UGR**

22.2

Luminaire beam angle

21° - 38° Clickbeam

Rated luminous flux

1,950 lm

Colour rendering index (CRI)

80

Approbations:**Type of Protection**

IP 20

Protection Class

II

Safety marks

F-mark

Other Marks

WEEE mark

Country Code

CE

Energy efficiency class LED

A++

Energy class of included lamp

A++

Lamps:**Socket****Light colour**

830

Colour temperature

3000K

Lifetime

50000 h (L70/B50)

Colour consistency (McAdam)

3

Number of lamps

1

Lamp

LED

Dimensions:**Diameter D**

65 mm

Height H

164 mm

Weight

490 g

