



(/fileadmin/assets/images/products/article-image/600px/742131.003.jpg)

Calido Clickbeam Maxi

742131.003

Series

Calido Clickbeam Maxi

Type of Installation

Track on ceiling

Colour

deep black, matt (RAL 9005)

European Article number EAN

4051859364467

Housing pressure die-cast aluminium powder-coated. 356° horizontal turning and 90° vertical pivoting. Front ring die-cast aluminium black. Hybrid optical system with polycarbonate lens and reflector aluminium faceted. Special polycarbonate lens suitable for various beam angles. Lens position adjustable via pressure mechanism for setting beam angle. Passive cooling. With multi-adapter for 3-phase 230 V power tracks. ceiling installation. Lamp (LED) included in scope of delivery.

[Technical Specifications](#)

[Downloads](#)

[Light Calculator](#)

[Accessories](#)

Technical Specifications

Electrical:**Luminaire efficacy**

97 lm/W

Control gear

Converter

Voltage

220 - 240 V / 50 - 60 Hz

System power

38 W

Luminaires on B10A fuse

2

Luminaires on B16A fuse

3

Luminaires on C10A fuse

4

Luminaires on C16A fuse

7

Inrush current / inrush current duration

21.2 A / 196 µs

Lighting technology:**UGR**

15.3

Luminaire beam angle

23° - 33° Clickbeam

Rated luminous flux

3,650 lm

Colour rendering index (CRI)

80

Approbations:**Type of Protection**

IP 20

Protection Class

II

Safety marks

F-mark

Other Marks

WEEE mark

Country Code

CE

Energy efficiency class LED

A++

Energy class of included lamp

A++

Lamps:**Socket****Light colour**

830

Colour temperature

3000K

Lifetime

50000 h (L70/B50)

Colour consistency (McAdam)

3

Number of lamps

1

Lamp

LED

Dimensions:**Diameter D**

110 mm

Height H

215 mm

Weight

1.23 kg

