

(/fileadmin/assets/images/products/article-image/600px/221174.002.jpg)

221174.002.1

Series Home 501 Type of Installation Ceiling mounting, Wall (surface)

Colour white

European Article number EAN 4051859168195

Fitting galvanised sheet steel, with bayonet mounting. Housing plastic (PC). Diffuser plastic, opal (PC). Housing and diffuser permanently connected.

Technical Specifications Downloads Light Calculator

Technical Specifications

Electrical:

Luminaire	efficacy
100	

Control gear EΒ Voltage 220 - 240 V / 50 Hz System power 12 W Luminaires on B10A fuse 16 Luminaires on B16A fuse 26 Luminaires on C10A fuse 27 Luminaires on C16A fuse 44 Inrush current / inrush current duration 23.2 A

Lighting technology:

UGR 21.5

Luminaire beam angle 112°

Rated luminous flux 1,200 lm

Colour rendering index (CRI) 80

Approbations:

Type of Protection IP 40

Protection Class

Glow Wire Test 850°C - 30 seconds

Impact Protection IK06 (1 Joule)

Safety marks F-mark

Other Marks WEEE mark

Country Code

CE

Energy efficiency class LED A+

Energy class of included lamp A+

Lamps:
Socket
Light colour 840
Colour temperature 4000K
Lifetime 35000 h (L70/B50)
Number of lamps 1
Lamp LED

Dimensions:

Diameter D

250 mm

Height H 48 mm

Weight

730



